

Magnetic Filters (Washing Machine & Boiler)

PPR housing with neodymium magnetic filter element · Standard ½" / ¾" connections

System overview

Polymer	PPR housing with neodymium magnetic filter element
Pressure classes	Domestic supply (typical 1–6 bar)
Size range	Standard ½" / ¾" connections
Continuous service temp.	Cold and warm potable water – see product label
Minimum / handling temp.	Above 0 °C in service
Joining method	Threaded connection (½" / ¾") and PPR fusion adapter where supplied

Standards & conformity

Scope	Standard
Quality system	ISO 9001
Conformity	CE marking

Recommended applications

- Washing-machine inlet connection sets
- Boiler / combi-boiler connection sets
- Capture of ferromagnetic particles upstream of appliance

Outside the scope of this product line

- Hydrocarbon or aggressive industrial fluids
- Replacing whole-house filtration where larger-flow filtration is required

Manufacturing & raw material

Manufactured at Velimeşe O.S.B. Mah. 227. Sok. No: 24/1, Çerkezköy / Tekirdağ / Türkiye. Quality system: ISO 9001.

Manufacturer warranty: Up to 50 years (per product line, when installed and used per published guidelines).

Project-specific dimensional tables, batch test certificates and DoP documents are available on request – contact info@vala.com.tr.